

Laying your Panaget floor

ACCESSORIES

UNDERLAYS

Panaget highly recommends you to remove all old flooring and carpets, and then install a quality underlay.

TYPE	DESCRIPTION
Isol 20	roll of 25 m ² , thickness 2,5 mm
Isol 30	roll of 15 m ² , thickness 3 mm
Bitumex	1200 x 600 x 8 mm square pads
Damp proof membrane 150 microns	115 ml x 3 folded in 2 = 345 m ² per roll

GLUES


TYPE	CONSUMMATION	APPLICATION	COLISAGE
PRESTO BIB	parquets flottants : collage en rives, 10 to 15 m ² /bottle of 0,50l	bottle	biberon de 500 g
PRESTO MO	stick down : 0,8 à 1kg/m ²	toothed spatula	7 to 14 kg
PRESTO PU	stick down : 0,8 à 1kg/m ²	toothed spatula	6 kg
PRESTO PM	Glue for compulsory use with under floor heating : 0,8 à 1kg/m ²	toothed spatula	6 kg
Black mastic	1,5 tube/m ²	toothed spatula	tube of 290 ml

LAMBOURDES

Pas de parquet cloué sans lambourdes. Lambourdes planées sur 2 faces, rainées en bout, traitées contre les parasites. Lambourdes en chêne : 80x26/1000 à 1490.

SKIRTING BOARDS


TYPE	DIMENSIONS en mm
veneered grooved end MDF core	14 x 80 x 2200
veneered, wooden core moulding, grooved end	14 x 100 x 2200
Moulding, grooved end, white ready to be painted	14 x 80 x 2200
Solidwood grooved end	14 x 70 x 2200



Panaget skirting boards are available in most of species.


FINISHING PROFILES

TYPE	DIMENSIONS en mm
Quarter round : french oak, oak cuivre, rubis beech, steamed beech, Bamboo natural, Bamboo caramel	15 x 15 x 2200
Scotia : oak, beech	14 x 14 x 2200
Stairs nosing	
-Franch oak	25 x 15 x 1300
-aluminium silver	36 x 18 x 1700
-aluminium gold	36 x 18 x 1700
Radiator collar	diameter 18
Door stop : oak, acajou	



DOORSILLS


TYPE	DIMENSIONS en mm
Wood doorsills	
Curved door sill for woodfloor 14 to 15 mm thickness	18 x 50 x 930
Curved door sill clic 12 mm for woodfloor 11 to 12 mm thickness	15 x 50 x 930
Lacquered door sill n°2 solidwood	15 x 35 x 1000 or 15 x 35 x 2000
T shape door sill for woodfloor 11 to 15 mm thickness	18 x 45 x 930
Curved door sill "2 in 1" for woodfloor 11 to 22 mm thickness	50 x 1000



Steel profiles

Steel profile in polished brass. Fills in gaps between two types of flooring, even if there is a difference in level (up to 14 mm).

Adhesive polished brass cover strip	930 X 30
Polished brass adapter profile	900 X 41



To know the species available for Panaget doorsills, we invite you to contact us.

FINISHING PRODUCTS

DESCRIPTION	CONSUMPTION	CONDITIONNEMENT
Supervitrifier satin	1 l = 10 à 12 m ² /coat	1 ou 5 l
sealer for exotic woodflooring	1 l = 10 à 12 m ² /coat	1 l
oil	1 l = 12 m ² /coat	1 l
primer for exotic oiled woods	1 l = 10 à 12 m ² /coat	1 l

CARE AND CLEANING PRODUCTS

DESCRIPTION	CONSUMPTION	CONDITIONNEMENT
Brightener for satin woodflooring	1l/50 m ²	1 l
DB stripper	1l/50m ²	1 l
Soap for oiled woodflooring	1l/400 m ²	1 l

LAYING ACCESSORIES

Laying kit : wedges, tapping bloc, etc.
Click flooring tapping block
B3 trowel
Special knife for boat deck fitting