



MAINTENANCE FOR OILED WOOD FLOORING

INTRODUCTION

The oil is 100% natural, devoid of all VOC (Volatile Organic Compounds) contents. Thanks to a molecular reaction the oil is embedded in the preliminary microns of the wood surface. Therefore, a surface film does not form like in vanished products. With this technology we can obtain a natural wood tone in one coat whilst respecting the natural aspect, and therefore avoiding the need to apply a second coat after fitting. It is also unnecessary to re-treat areas of the floor which appear to be insufficiently oiled; this is not the case. It is purely an illusion, linked to the fact that the natural structure of the wood comes in different forms and which indeed contributes to a much more authentic aspect.

UPKEEP

Day to day cleaning is carried out by Hoover/vacuum. From time to time (2-3 times a week) clean surface using a well-rung out damp cloth with cold water (no detergents). Any excess oil will be removed automatically by the first cleaning. Too often, or too wet could damage the surface. The following stains should be removed straight away with a sponge: wine, coca cola, coffee, tea, vinegar, oil, milk, lemon juice, etc.

To remove tougher stains (paint, glue, etc.), use diluted acetone. If necessary, lightly sand the area and then re-apply maintenance oil.

RENOVATION

Shake VIGOROUSLY the oil to mix up the contents. On the completely dry surface, apply a few drops of oil which are then rubbed in to the grain using a soft cloth (remember 100ml of oil will cover 100m²). Take care to keep to the sanded area and not overlap the area which is not damaged.

Within 15 minutes, carefully wipe off excess oil.

Ventilate the site so that the floor can dry within 6-8 hours.

Do not re-use oil soap on the treated surface for at least one week.

**Attention! Product will mark textiles (clothes, carpets, rugs, etc.). After using oil, all oily rags, cloths, etc. must be emerged in water to avoid spontaneous combustion.*