



Daylight whites

PANAGET

manufacture française de parquet
DEPUIS 1929



No 1019702

FRENCH OAK CLASSIC LINEN, DIVA 139 CLIC / 14 MM

Characteristics

Species: French oak **Origin:** France

Grade: Classic - light and dark wood, black knots, medular rays and discolouration.

Finish: Linen - brushed, light white matt lacquered / Ecostrong lacquer - Shine (gloss): 4/6

While we take the greatest care in manufacturing our flooring, there can sometimes be slight variations in colouring. So it's important to factor in margin of 2-5% more than the actual you're covering. This means you won't run out of planks and you will be sure to enjoy a beautiful finished product.

Design

Engineered wide single plank made under the patent EN 13489

Click system made under Unilin patent NoEP1640530



Description

Width: 139 mm

Length: 495 to 1992 mm

Thickness: 14 mm

Top layer: 3.4 mm

Core: HDF*

Counterbalance: unrolled wood

Profile: 4 bevels

*High Density Fiber Board

Packing

Sqm/pack: 1.38

Pack/pallet: 55

Sqm/pallet: 75.90

Weight/sqm: 11.6 kg

Weight/pallet: 880.4 kg

Installation method





Glue-free floating under
the patent DTU 51.11



Glue down installation
under the patent DTU 51.2



Floating installation using
plastic DPM and Isol 20 or fully
glue down using Presto PM



DECLARATION OF PERFORMANCE

NO 1019702



Unique identification code of the product-type: Diva 139 Clic, 14 mm, French oak

Intended use/es: Engineered wide single plank made under the patent EN 13489
Glue-free floating under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: No4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction to fire	Dfl-s1	EN 14342 : 2013
Features for this classification: - Average minimum density (Kg/m ³)	500	
- Average thickness (mm)	14	
- Intended use, fitting mode	Floating fit	
Formaldéhyde emission	E1	EN 717-1
Content of pentachlorophénol	PCP ≤ 5 ppm	-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEV0910046A)	Class A+ < 1µg/m ³	ISO 16000
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7
Thermal resistance (m ² .K/W)	0.11	
Biological sustainability	Class 1	EN 335

3501ME0H8CPO0EFYH8 N
SFODIFOW\$PONFOUBISFHVM8POW8TUPSFEVDFUIF8CPOGPPUSDUPGOFXCVMEDHTPWFSUIF\$FTUN8BFEZ8M8FDD8MF
%GF8MFNB8UBTF8TTNFOULHR8 N

N/A : Not Applicable

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 16 december 2021

Carole FRANÇOIS