



Timeless natural hues

No 1014172

FRENCH OAK ZENITUDE - SALVAGIO NATURAL OIL, DIVA 139 TONGUE & GROOVE / 14 MM

Characteristics

Species: French oak **Origin:** France

Grade: Zenitude - Salvagio - light and dark wood, black knots, filled knots, partially opened knots, discolouration, cracks, splits, sapwood. Grade with all peculiarities of the wood without limitation. The size of the knots is proportional to the width of the planks. Structured and locally irregular wear layer. UV-cured oiled flooring.

Finish: Natural oil - brushed, natural matt oiled / Hard wax oil - Shine (gloss): 5/8

For oiled wood floors, apply a thin coat of Panaget maintenance oil right after installation. Please refer to our maintenance guide.

Design

Engineered wide single plank made under the patent EN 13489 Tongue & Groove



Description

Width: 139 mm
Length: 500 to 2000 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: plywood
Counterbalance: unrolled wood
Profile: 2 bevels

Packing

Sqm/-pack: 1.39
Pack/pallet: 55
Sqm/pallet: 76.45
Weight/sqm: 7.4 kg
Weight/pallet: 565.7 kg

Installation method





Floating glued installation under the patent DTU 51.11



Glue down installation under the patent DTU 51.2



Floating installation gluing T&G using plastic DPM and Isol 20 or fully glue down using Presto PM



DECLARATION OF PERFORMANCE

NO 1014172



Unique identification code of the product-type: Diva 139 Tongue & Groove, 14 mm, French oak

Intended use/es: Engineered wide single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: No4

Harmonised standard: EN 14342 : 2013

Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation	
Reaction to fire	Dfl-s1	EN 14342 : 2013	
Features for this classification: - Average minimum density (Kg/m ³) - Average thickness (mm) - Intended use, fitting mode	500 14 Floating fit		
Formaldéhyde emission	E1		EN 717-1
Content of pentachlorophénol	PCP ≤ 5 ppm		-
Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree No DEVPO910046A)	Class A+ < 1µg/m ³	ISO 16000	
Breaking strength	N/A	-	
Slipperiness	N/A	-	
Thermal conductivity (W/m.K)	0.13	EN 14342 / Chapter 4.7	
Thermal resistance (m ² .K/W)	0.11		
Biological sustainability	Class 1	EN 335	

35ME0HBCPO0EFYH0 N
SFODIFOW\$PONFOUBISFHVMBIP0WBTUPSEVDFUIFDBCP0GPPUSDDUPGOFXCVME0DHTPWFSUIF\$FTUNBFZBM0FDD0MF
%GF0MFNB0BTFTTNFOULHR0 N

N/A : Not Applicable

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole FRANÇOIS - Executive Director

Bourgbarré, 16 december 2021

Carole FRANÇOIS