



Elegant browns



N° 1014166

FRENCH OAK AUTHENTIC CUIR, DIVA 184 TONGUE & GROOVE / 14 MM

Characteristics

Species: French oak **Origin:** France

Grade: Authentic - light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. The size of the knots is proportional to the width of the plank.

Finish: Cuir - brushed, old leather-tone matt oiled / Oil - Gloss: 4/8

For oiled wood floors, apply a thin coat of Panaget maintenance oil right after installation. Please refer to our maintenance guide.

Design

Engineered extra-wide single plank made under the patent EN 13489
Tongue & Groove



Description

Width: 184 mm
Length: 500 to 2000 mm
Thickness: 14 mm
Top layer: 3.4 mm
Core: plywood
Counterbalance: unrolled wood
Profile: 4 bevels

Packing

Sqm/pack: 1.84
Pack/pallet: 44
Sqm/pallet: 80.96
Weight/sqm: 7.4 kg
Weight/pallet: 599.1 kg

Installation method





Floating glued
installation under the
patent DTU 51.11



Glue down installation
under the patent DTU 51.2



Floating installation gluing T&G
using plastic DPM and Isol 20 or
fully glue down using Presto PM



PANAGET - 3 rue d'Orgères - 35230 Bourgarré - FRANCE
tel: +33 (0)2 99 05 77 77 // fax: +33 (0)2 99 57 73 55 // www.panaget.com

DECLARATION OF PERFORMANCE

N° 1014166



Unique identification code of the product-type: Diva 184 Tongue & Groove, 14 mm, French oak

Intended use/es: Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

Manufacturer: PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

System/s of Assessment and Verification of Constancy of Performance: n°4

Harmonised standard: EN 14342 : 2013

Declared performances:

| Essential features | Performances | Appropriate Technical Documentation and/or Specific Technical Documentation |
|---|--|---|
| Reaction of fire | Dfl-s1 | EN 14342 : 2013 |
| Features for this classification: - Average minimum density (Kg/m ³) | 500 | |
| - Average thickness (mm) | 14 | |
| - Intended use, fitting mode | Floating fit | |
| Formaldéhyde emission | E1 | EN 717-1 |
| Content of pentachlorophenol | PCP ≤ 5 ppm | - |
| Release of other dangerous substances: - VOC* emissions (Decree No 2011-321) - CMR 1&2** emissions (Decree n° DEVP0910046A) | Class A+ < 1 µg/m ³ | ISO 16000 |
| Breaking strength | N/A | - |
| Slipperiness | N/A | - |
| Thermal conductivity (W/m.K) | 0.13 | EN 14342 / Chapter 4.7 |
| Thermal resistance (m ² .K/W) | 0.11 | |
| Biological sustainability | Class 1 | EN 335 |
| RE2020 - Building Carbon Index | 3 kg.CO ₂ /m ² | - |
| FDES 2022 - Life Cycle impact assessment | 8.6 kg éq. CO ₂ /m ² | - |

N/A : Not Applicate

*VOC: Volatile Organic Compounds

**CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regluation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole François - Executive Director

Bourgbarré, 15 december 2023

Carole FRANÇOIS

