



Elegant browns

# PANAGET

manufacture française de parquet  
DEPUIS 1929



N° 1017303

## FRENCH OAK AUTHENTIC ARGILE, DIVA 223 TONGUE & GROOVE / 15 MM

### Characteristics

**Species:** French oak **Origin:** France

**Grade: Authentic** - light and dark wood, black knots, filled knots, partially opened knots, traces of discolouration, black marks, cracks. The size of the knots is proportional to the width of the plank.

**Finish: Argile** - brushed, clay-tone matt lacquered / Ecostrong lacquer - Gloss: 4/6

Argile is a tint that acts on wood's natural tannin properties to create an aged finish. In some cases, the shade may change slightly over time.

### Design

Engineered extra-wide single plank made under the patent EN 13489  
Tongue & Groove



### Description

**Width:** 223 mm

**Length:** 2000 mm

**Thickness:** 15 mm

**Top layer:** 4.5 mm

**Core:** plywood

**Counterbalance:** unrolled wood

**Profile:** 2 bevels

### Packing

**Sqm/pack:** 1.78

**Pack/pallet:** 39

**Sqm/pallet:** 69.42

**Weight/sqm:** 10.9 kg

**Weight/pallet:** 756,7 kg

### Installation method





Floating glued  
installation under the  
patent DTU 51.11



Glue down installation  
under the patent DTU 51.2



Fully glue down with Presto PM



# DECLARATION OF PERFORMANCE

## N° 1017303



**Unique identification code of the product-type:** Diva 223 Tongue & Groove, 15 mm, French oak

**Intended use/es:** Engineered single plank made under the patent EN 13489

Floating glued installation under the patent DTU 51.11

**Manufacturer:** PANAGET - 3 rue d'Orgères 35230 Bourgbarré / FRANCE

**System/s of Assessment and Verification of Constancy of Performance:** n°4

**Harmonised standard:** EN 14342 : 2013

### Declared performances:

Essential features	Performances	Appropriate Technical Documentation and/or Specific Technical Documentation
Reaction of fire	Dfl-s1	EN 14342 : 2013
Features for this classification:		
- Average minimum density (Kg/m <sup>3</sup> )	500	
- Average thickness (mm)	15	
- Intended use, fitting mode	Floating fit	
Formaldéhyde emission	E1	EN 717-1
Content of pentachlorophenol	PCP ≤ 5 ppm	-
Release of other dangerous substances:		ISO 16000
- VOC* emissions (Decree No 2011-321)	Class A+	
- CMR 1&2** emissions (Decree n° DEVP0910046A)	< 1 µg/m <sup>3</sup>	
Breaking strength	N/A	-
Slipperiness	N/A	-
Thermal conductivity (W/m.K)	0.15	EN 14342 / Chapter 4.7
Thermal resistance (m <sup>2</sup> .K/W)	0.10	
Biological sustainability	Class 1	EN 335
RE2020 - Building Carbon Index	3 kg.CO <sub>2</sub> /m <sup>2</sup>	-
FDES 2022 - Life Cycle impact assessment	8.6 kg éq. CO <sub>2</sub> /m <sup>2</sup>	-

N/A : Not Applicate

\*VOC: Volatile Organic Compounds

\*\*CMR 1&2: Carcinogenics, Mutagens or Reproductive toxin of 1&2 category

The performances of product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regluation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and behalf of the manufacturer by: Carole François - Executive Director

Bourgbarré, 15 december 2023  
**Carole FRANÇOIS**

